(FAC-SIMILE OF THE LATEST LABEL.)

Medium Drab	Medium Lead
Light Drab	Colonial Yellow
Dark Drab	Dark Lead
Light Quaker Drab	Salmon
Light Straw	Buff
Dark Olive Green	Quaker Drab
Gray	Medium Olive
Light Buff	Apple Green
Medium Green Stone	Stone
Light Brown	Light Lead
Light Tan	Cream
Red	Bronze Green
Light Green Stone	Spruce
Olive Tint	Dark Straw
Light Olive Green	Maroon
Vermilion	Medium Green
Yellow	Light Green
Brown	Dark Green
Light Blue	Dark Blue

TD CAT 1895 #PAPV03B304

READY MIXED

ENAMEL COTTAGE PAINTS

DIRECTIONS FOR USE.

Shake the package well before opening.

Stir thoroughly both before and during use.

Apply in the ordinary way; just as pure White Lead and Linseed Oil paint is always applied.

Cover all knots and sappy places of new work with Shellac Varnish, and see that old work is also properly prepared before fresh paint is applied.

A coat to prime and fill the surface is always desirable, and sometimes absolutely necessary.

Let the surface to be painted be perfectly dry to begin with, and allow one coat of paint to dry before applying another.

Putty up all nail-holes before applying finishing coat first coloring the putty to match the color of the paint.

If the paint should be found too thick, do not add Spirits of Turpentine, but a little pure Boiled Linseed Oil, especially on first coat.

QUANTITY REQUIRED.

One gallon will cover 250 square feet—two coats, and to ascertain the amount of paint requisite for a building, add front, rear and sides together; multiply by the height and divide by 250. The result will give the number of gallons required for two-coat work. Divide by 180 if the work is very rough or old.

In addition to colors shown on this card we also furnish:

BLACK, INSIDE WHITE, OUTSIDE WHITE.